

RELATIVE HUMIDITY

RH1000

New Artisan[™] Digital Thermo-hygrometer

This economical *Artisan*TM pen-size thermohygrometer is ideal for quick and fast relative humidity and temperature measurements. The compact size allows it to fit easily into your shirt pocket or tool box. Turn the unit on, then point and measure. Digital display eliminates variation from reading analog dials. The 1" x 3/4" LCD displays both RH and temperature simultaneously.

The rugged capacitance polymer sensor will provide years of stable readings. Microprocessor -based system provides HOLD / MAX / MIN features through its 5-button keypad. Typical response time of 120 seconds. Periodic re-calibration is easy with calibration kits. ABS storage case. ABS housing. One year warranty. Compact Size! Low-Priced!

Artisan™ RH1000 Thermohygrometer provides digital indication of room temperature and relative humidity.

CE

SPECIFICATIONS

	RH	Temp
Measurement Range:	0 to 100%	-20 to 50°C
		(32 to 122°F)
Resolution:	1%	0.1°C or °F
Accuracy:	±3% @ cal temp.	±1°C
Sensor:	Capacitance polymer	
Response time:	120 seconds typical	
Operating Temp.:	0 to 50°C (32 to 122°F)	
Operating Humidity:	0 to 100% RH, non-condensing	
Storage Temp.:	-20 to 60°C (-4 to 140°F)	
Auto shutoff:	after 20 min of non-operation	
	(disable feature available)	
Power:	3 Volt battery (1 x CR2032)	
Dimensions:	175 x 42 x 16 mm (meter only)	
(L x W x D)	(6.9 x 1.5 x 0.7 in.)	
(case dim.)	254 x 167 x 75 mm (10 x 6.6 x 3 in.)	
Weight (meter):	56 g (2 oz)	
Shipping Wt:	0.9 kg (2 lb)	

RH1000 Ordering Information

Part No. Description

 RH1000.001
 RH1000 Meter, ABS case & battery.

 RH1000.002
 RH1000 Kit. Includes Meter, Cal Kits (33 & 75%), ABS case & battery.

 RH1000.900
 Calibration Kit, 33% RH.

 RH1000.901
 Calibration Kit, 75% RH.

APT logo, Artisan – TM Advanced Product Technology LLC © Copyright 2003 APT Instruments. Specifications subject to change.

SPECIAL FEATURES

Digital display of both relative humidity and temperature HOLD / MAX / MIN features Easy self-calibration Capacitance polymer sensor °C/°F switchable Rugged ABS storage case

APPLICATIONS

HVAC Monitoring Clean Rooms & Laboratories Computer Rooms Office Environment Greenhouses Wood/Paper Manufacturing

For more information contact: APT Instruments

P.O. Box 317, Rochester, IL 62563 USA 877.324.5444 Toll-free (US/Can) 217.498.0342 * 217.498.0352Fx www.aptinstruments.com sales@aptinstruments.com