



### New Artisan™ Digital Thermo-hygrometer

This economical Artisan™ RH / temperature transmitter provides continuous RH and temperature monitoring for a very attractive price. Mount the transmitter on a wall, in a duct or fume hood. The transmitter provides a dual channel analog output (0 to 1 Vdc) that can be easily adapted to your PC, data logger or chart recorder. The electronics are designed to withstand high temperatures up to 65°C (149°F).

The rugged capacitance polymer sensor will provide years of stable readings. Typical response time of 120 seconds. Vdc power required for transmitter operation. Periodic re-calibration is easy with calibration kits. ABS housing. One year warranty.

**Compact Size!**  
**Low-Priced!**



Artisan™  
RH100  
RH/Temp  
Transmitter

### SPECIFICATIONS

	RH	Temp
Measurement Range:	5 to 95%	32 to 149°F (0 to 65°C)
Resolution:	0.1%	0.1°C or °F
Accuracy:	±3% @ cal temp.	±0.6°C (±1°F)
Output Voltage: (relative humidity)	10 mV / % RH; 0 to 1 Vdc	
(temperature)	10 mV / °F; 0 to 1V	
Output load:	100 kOhm typ.	
Sensor:	Capacitance polymer	
Response time:	120 seconds typical	
Operating Temp.:	32 to 149°F (0 to 65°C)	
Operating Humidity:	5 to 95% RH, non-condensing	
Storage Temp.:	-4 to 149°F (-20 to 65°C)	
Power:	6 to 16Vdc	
Dimensions: (L x W x D)	98 x 68 x 35 mm (meter only)	
(cable length)	(3.9 x 2.7 x 1.4 in.)	
Weight (meter):	115 g (4 oz)	
Shipping Wt:	0.45 kg (1 lb)	

### SPECIAL FEATURES

*Transmits both relative humidity and temperature*  
*Dual analog output*  
*Easy to setup!*  
*Easy self-calibration*  
*Capacitance polymer sensor*  
*Rugged ABS housing*

### APPLICATIONS

*HVAC Monitoring*  
*Clean Rooms & Laboratories*  
*Computer Rooms*  
*Office Environment*  
*Greenhouses*  
*Wood/Paper Manufacturing*

### RH100 Ordering Information

Part No.	Description
RH100.001	RH100 Transmitter.
RH1000.902	Calibration Kit, 33% RH.
RH1000.903	Calibration Kit, 75% RH.

### For more information contact:

APT Instruments  
P.O. Box 317, Rochester, IL 62563 USA  
877.324.5444 Toll-free  
217.498.0342 \* 217.498.0352Fx  
[www.aptinstruments.com](http://www.aptinstruments.com)  
[sales@aptinstruments.com](mailto:sales@aptinstruments.com)